



Battery Selection Chart

Battery Selection by Engine Sales Model and Ambient Temperature

| Engine Sales Model | -30 to -12 C (-22 to 10 °F)** | | | -12 to 20 C (10 to 68 °F)** | | | > 20 C (> 68°F) | | |
|--------------------|-----------------------------------|---|---|-----------------------------------|---|---|-----------------------------------|---|---|
| | Dry Hybrid Battery (Qty) GroupNo. | Dry Maint. Free Battery (Qty) Group No. | Wet Maint. Free Battery (Qty) Group No. | Dry Hybrid Battery (Qty) GroupNo. | Dry Maint. Free Battery (Qty) Group No. | Wet Maint. Free Battery (Qty) Group No. | Dry Hybrid Battery (Qty) GroupNo. | Dry Maint. Free Battery (Qty) Group No. | Wet Maint. Free Battery (Qty) Group No. |
| 3304 | (1) 7L7871 1000 CCA | NONE | (2) 153-5700 * 1125 CCA | NONE | (1) 160-5447 950 CCA | (2) 115-2422 * 1000 CCA | NONE | NONE | (1) 7C1976 650 CCA |
| C7 | | | | | | | | | |
| C8.7 | | | | | | | | | |
| C9 | | | | | | | | | |
| C9.3 | | | | | | | | | |
| C10 | | | | | | | | | |
| 3306 | | | | | | | | | |
| C11 | (1) 7L7872 1300 CCA | NONE | (2) 153-5710 * 1400 CCA | (1) 7L7871 1000 CCA | NONE | (2) 153-5700 * 1125 CCA | NONE | (1) 160-5447 950 CCA | (2) 115-2422 * 1000 CCA |
| C12 | | | | | | | | | |
| C13 | | | | | | | | | |
| 3406 | | | | | | | | | |
| C15 | | | | | | | | | |
| C16 | | | | | | | | | |
| 3408 | | | | | | | | | |
| C18 | | | | | | | | | |

* Group not available. Individual battery part number listed instead. Batters are 12 volts, and must be placed into series.

** Starting Aid Recommended for temperatures under 0 deg C